



ENGINEERING & TECHNICAL DATA — Flex-Tube® PU 60

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.5	.050	5	N/A	28	40
2.5	.57	.050	5.5	N/A	28	40
3	.7	.055	6	N/A	28	40
4	.9	.055	11.75	N/A	28	40
5	1.27	.060	15.5	N/A	28	36
6	1.7	.060	16.75	N/A	28	30
8	2.44	.060	20.5	N/A	26	28

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Very heavy weight polyether polyurethane hose with a rigid external ABS helix

Temperature Range: -40°F to 200°F

Standard Color: Clear with Yellow Helix

Standard Lengths: 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

