



ENGINEERING & TECHNICAL DATA – Springflex® AWP-W

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
8	.4	N/A	5	10:1	N/A	3
10	.6	N/A	6	10:1	N/A	2
12	.7	N/A	7.5	10:1	N/A	1.5
14	.8	N/A	8.5	10:1	N/A	1.2
16	.9	N/A	9.5	10:1	N/A	1
18	1.1	N/A	10.5	10:1	N/A	.8
20	1.2	N/A	11.5	10:1	N/A	.7
24	1.4	N/A	14	10:1	N/A	.5

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Single-ply acrylic coated polyester fabric hose reinforced with a spring steel wire helix & external PVC wearstrip

Temperature Range: -20°F to 325°F

Standard Color: Yellow with Black Wearstrip

Standard Lengths: 25 Feet

- Flame retardant to UL 94V-0

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

