



ENGINEERING & TECHNICAL DATA – Bendway® A

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.113	.008	2	N/A	N/A	N/A
3	.167	.008	3	N/A	N/A	N/A
4	.2	.008	4	N/A	N/A	N/A
5	.25	.008	5	N/A	N/A	N/A
6	.3	.008	6	N/A	N/A	N/A
7	.35	.008	8	N/A	N/A	N/A
8	.35	.008	10	N/A	N/A	N/A
9	.4	.008	12	N/A	N/A	N/A
10	.44	.008	15	N/A	N/A	N/A
12	.53	.008	20	N/A	N/A	N/A

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Single-ply helically corrugated aluminum alloy hose with a four-ply finished seam that is folded flat and crimped for tightness and strength

Temperature Range: -100°F to 400°F

Standard Color: Silver

Standard Lengths: 5 & 10 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A SCHAUENBURG HOSE TECHNOLOGY COMPANY