



## ENGINEERING & TECHNICAL DATA – Bendway® S

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.17	.005	2.1	N/A	N/A	N/A
3	.31	.005	3.3	N/A	N/A	N/A
4	.35	.005	4.3	N/A	N/A	N/A
5	.45	.005	5.4	N/A	N/A	N/A
6	.54	.005	6.5	N/A	N/A	N/A
7	.62	.005	7.5	N/A	N/A	N/A
8	.64	.005	8.7	N/A	N/A	N/A
10	.8	.005	10.8	N/A	N/A	N/A
12	.95	.005	13	N/A	N/A	N/A

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Single-ply helically corrugated stainless steel alloy hose with a 4-ply finished seam that is folded flat and crimped for tightness and strength

**Temperature Range:** -400°F to 800°F

**Standard Color:** Silver

**Standard Lengths:** 5 & 10 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464  
sales@flexaust.com ~ www.flexaust.com



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY