



## ENGINEERING & TECHNICAL DATA — Heat-Flex<sup>®</sup> CW-325

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.25	N/A	1.6	4:1	29	30
2.5	.26	N/A	1.78	4:1	29	30
3	.28	N/A	2.3	5:1	29	30
4	.41	N/A	2.8	5:1	29	18
5	.6	N/A	3.5	5:1	16	14
6	.69	N/A	3.8	6:1	14	7
8	.92	N/A	5.2	6:1	7	5
10	1.1	N/A	6.4	6:1	6	4
12	2	N/A	8	6:1	5	3.7

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Single-ply acrylic coated polyester fabric hose reinforced with a spring steel wire helix

**Temperature Range:** -20°F to 325°F

**Standard Color:** Black

**Standard Lengths:** 25 Feet

- Listed as UL 94V-0 flame retardant

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464  
sales@flexaust.com • www.flexaust.com



A SCHAUBENBURG HOSE TECHNOLOGY COMPANY