



ENGINEERING & TECHNICAL DATA — Dayflex® DFD-T

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
1	.04	N/A	1	2:1	N/A	11
1.25	.06	N/A	1.5	2:1	N/A	10
1.5	.08	N/A	2	3:1	N/A	10
1.75	.09	N/A	2.5	3:1	N/A	10
2	.1	N/A	3	3:1	N/A	10
2.25	.11	N/A	3.5	3:1	N/A	9
2.5	.13	N/A	3.75	3:1	N/A	9
3	.14	N/A	4.25	3:1	N/A	8
4	.22	N/A	4.5	3:1	N/A	3

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Light weight propylene-ethylene elastomer hose reinforced with an internal polypropylene helix

Temperature Range: -40°F to 225°F

Standard Color: Black

Standard Lengths: 25 & 50 Feet

- Certified to FMVSS 302 flame standards

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

