



## ENGINEERING & TECHNICAL DATA — Genesis® DPZ

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
1.25	.16	N/A	2.5	N/A	29	20
1.5	.2	N/A	3	N/A	29	18
2	.26	N/A	3.5	N/A	29	15

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Light weight polyethylene copolymer hose reinforced with an integral polyethylene helix

**Temperature Range:** -40°F to 140°F

**Standard Color:** Gray

**Standard Lengths:** 25 & 50 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

**Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464**  
**sales@flexaust.com • www.flexaust.com**



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY