



## ENGINEERING & TECHNICAL DATA — Flex-Lok® 750

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
3	.8	N/A	3	3:1	10	16
4	1.0	N/A	3.5	3:1	9	15
5	.9	N/A	4	5:1	8	13.5
6	1.1	N/A	5	5:1	7	12
8	1.7	N/A	7	5:1	4	10
10	2	N/A	9	5:1	3.5	9.5
12	2.3	N/A	11	5:1	3	8
14	2.9	N/A	13	5:1	2	3.5
16	3.6	N/A	15	5:1	1	2.5

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Double-ply construction wire inserted fiberglass fabric hose with a heat-resistant fiberglass liner mechanically crimped in a continuous process

**Temperature Range:** -40°F to 750°F

**Standard Color:** Red

**Standard Lengths:** 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464  
sales@flexaust.com • www.flexaust.com

