



ENGINEERING & TECHNICAL DATA — Flexadux[®] TR HT-W

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
8	1.3	.045	7	3:1	6	7
10	2	.045	9	3:1	6	6
12	2.4	.045	11	3:1	5	5.5

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Heavy weight thermoplastic rubber hose reinforced with a spring steel wire helix & external polypropylene wearstrip

Temperature Range: -60°F to 275°F

Standard Color: Black with Yellow Wearstrip

Standard Lengths: 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A SCHAUBURG HOSE TECHNOLOGY COMPANY