



ENGINEERING & TECHNICAL DATA — Dayflex[®] MG-U

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
.75	.1	N/A	.875	1.6:1	29	20
1	.14	N/A	1	1.6:1	29	20
1.25	.17	N/A	1.25	1.6:1	29	20
1.5	.21	N/A	1.5	1.6:1	29	20
2	.33	N/A	2.25	1.6:1	29	20

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Elastomer polyurethane hose reinforced with a vinyl coated spring steel wire helix

Temperature Range: -60°F to 160°F

Standard Color: Black

Standard Lengths: 50 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY