



ENGINEERING & TECHNICAL DATA — Genesis[®] Tiger Tail[®]

| INSIDE DIAMETER (IN) | APPROX. WEIGHT (LBS/FT) | WALL THICKNESS (IN) | CL BEND RADIUS (IN) | COMPRESSION RATIO | NEGATIVE PRESSURE (IN/HG) | WORKING PRESSURE (PSI) |
|----------------------|-------------------------|---------------------|---------------------|-------------------|---------------------------|------------------------|
| 1.5 | .35 | N/A | 3.75 | N/A | 29 | 26 |
| 2 | .65 | N/A | 5 | N/A | 29 | 17 |
| 3 | 1.2 | N/A | 8 | N/A | 29 | 12 |
| 4 | 1.6 | N/A | 9.5 | N/A | 29 | 7 |

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Rugged polyethylene copolymer hose reinforced with an integral polyethylene helix

Temperature Range: -40°F to 140°F

Standard Color: Yellow and Black

Standard Lengths: 25 & 50 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

