



## ENGINEERING & TECHNICAL DATA — Flex-Tube® PU 60 HF

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.5	.055	4.5	N/A	28	40
2.5	.6	.055	5	N/A	28	40
3	.8	.055	5.8	N/A	28	40
4	1	.060	6	N/A	20	30
5	1.2	.060	6.5	N/A	12	24
6	1.4	.060	7	N/A	10	24
7	1.6	.060	8	N/A	8	20
8	2	.060	9	N/A	6	20

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Highly flexible very heavy weight thermoplastic polyether polyurethane hose with a rigid external ABS helix

**Temperature Range:** -40°F to 200°F

**Standard Color:** Clear with Blue Helix

**Standard Lengths:** 25 & 50 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464  
sales@flexaust.com • www.flexaust.com



A SCHAUBURG HOSE TECHNOLOGY COMPANY