



ENGINEERING & TECHNICAL DATA — Genesis® StatPath® Plus

| INSIDE DIAMETER (IN) | APPROX. WEIGHT (LBS/FT) | WALL THICKNESS (IN) | CL BEND RADIUS (IN) | COMPRESSION RATIO | NEGATIVE PRESSURE (IN/HG) | WORKING PRESSURE (PSI) |
|----------------------|-------------------------|---------------------|---------------------|-------------------|---------------------------|------------------------|
| 1 | .15 | N/A | 2.25 | N/A | 29 | 14 |
| 1.25 | .22 | N/A | 3 | N/A | 29 | 14 |
| 1.5 | .31 | N/A | 3.25 | N/A | 29 | 9 |
| 2 | .40 | N/A | 4.5 | N/A | 29 | 8 |

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Light weight polyethylene conductive copolymer hose with a yellow skimcoat reinforced with an integral polyethylene helix

Temperature Range: -40°F to 140°F

Standard Color: Black with Yellow Skimcoat

Standard Lengths: 25 & 50 Feet

- Surface Resistivity Level: 10^3 - 10^5 Ohms/Square

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

