



ENGINEERING & TECHNICAL DATA — Flex-Lok[®] 570

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
3	.50	N/A	2	6:1	14	14
4	.71	N/A	3	6:1	11	12.5
5	.69	N/A	3.5	8:1	9.5	9
6	.84	N/A	4	8:1	7	8.2
7	.97	N/A	4.5	8:1	6.5	7.4
8	1.1	N/A	5	8:1	6	7
9	1.26	N/A	5.5	8:1	4	6.6
10	1.4	N/A	6	8:1	5	6.3
12	1.5	N/A	8	8:1	2.8	5.1

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Single-ply para-aramid fabric hose mechanically crimped in a continuous process

Temperature Range: -40°F to 570°F

Standard Color: Outer Layer: Green, Inner Layer: Black

Standard Lengths: 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The numbers of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY