



ENGINEERING & TECHNICAL DATA — Flexadux[®] PV R-4 Stretch

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2.5	.26	.015	2	6:1	10	5
3	.28	.015	2.5	6:1	7	3.5
4	.35	.015	3.5	7:1	4	2.5
5	.65	.015	4.5	4:1	3	2
6	.74	.015	3.5	4:1	2	1.5

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Medium weight PVC hose reinforced with a spring steel wire helix

Temperature Range: 20°F to 160°F

Standard Color: Clear

Standard Lengths: 3 Feet Compressed

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY