



ENGINEERING & TECHNICAL DATA — Flexadux® PU Flex-Thane LD-SD

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.25	.015	2	3:1	29	30
2.5	.35	.020	2.8	4:1	19	30
3	.4	.020	3.3	4:1	29	30
4	.5	.020	3.8	4:1	24	22
5	.6	.020	4.5	4:1	13	18
6	.7	.020	5.3	4:1	8	15
8	.9	.020	6.5	5:1	2	7
10	1.2	.020	7.5	5:1	2	7
12	1.4	.020	9	5:1	1.7	6

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Light weight static dissipative polyurethane hose reinforced with a bronze coated spring steel wire helix

Temperature Range: -65°F to 200°F

Standard Color: Clear

Standard Lengths: 25 Feet

- Surface resistivity level: 10^8 - 10^{10} Ohms/Square

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A SCHAUBURG HOSE TECHNOLOGY COMPANY