



ENGINEERING & TECHNICAL DATA — Flex-Tube® PV-SD-LW

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2.5	.35	.025	2.6	2.5:1	14	9
4	.53	.025	3.3	2.5:1	12	7

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Light weight coextruded static dissipative PVC hose with a rigid external PVC helix

Temperature Range: -10°F to 160°F

Standard Color: Clear with Blue Helix

Standard Lengths: 10 & 15 Feet

- Surface Resistivity Level: 10^9 - 10^{10} Ohms/Square

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

