



## ENGINEERING & TECHNICAL DATA - Springflex® FX-180SF

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
12	.9	N/A	9	10:1	N/A	7
20	1.4	N/A	13	10:1	N/A	3

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** High strength sewn single-ply PVC vinyl coated polyester fabric hose reinforced with a spring steel wire helix & external PVC wearstrip

**Temperature Range:** -20°F to 180°F

**Standard Color:** White with White Wearstrip

**Standard Lengths:** 25 Feet

- Flame retardant to UL 94V-0

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

**Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464**  
**sales@flexaust.com • www.flexaust.com**

