

FX-SERIES

FLEXAUST®

**Air Conditioning, Dehumidification
&
Heater Ducting**



Made in USA



A **SCHAUBURG** HOSE TECHNOLOGY COMPANY

A/C Ducting

Construction: High strength sewn single-ply PVC vinyl coated polyester hose with a spring steel wire helix & heavy-duty PVC wearstrip.

Temperature Range (°F): -20°F to 180°F **Standard Color:** White with White Wearstrip

Size Range: 12" to 24" **Additional Colors Available:** ● ● ● **Standard Length:** 25'

- Lock stitch construction creates better air flow & allows for better performance in lower & higher temperatures
- Light weight duct designed for dehumidification applications
- Great compressibility
- Moisture resistant & UV stabilized to prevent mold & mildew
- Dust resistant material creates an easy clean surface
- Flame retardant to UL 94V-0
- PVC coated polyester is superior to PVC laminated polyester products
- Standard with wire ropes, belted cuffs & storage straps

FX-180

Bi-Directional Air Flow

Construction: High strength heat-welded single-ply PVC vinyl coated polyester hose with a spring steel wire helix & heavy-duty PVC wearstrip.

Temperature Range (°F): -20°F to 180°F **Standard Color:** White with White Wearstrip

Size Range: 12" to 24" **Additional Colors Available:** ● ● ● **Standard Length:** 25'

- Bi-directional construction provides super air flow & excellent compressibility
- Light weight duct designed for dehumidification applications
- Moisture resistant & UV stabilized to prevent mold & mildew
- Dust resistant material creates an easy clean surface
- Flame retardant to UL 94V-0
- PVC coated polyester is superior to PVC laminated polyester products
- Standard with wire ropes, belted cuffs & storage straps

FX-180 SF

Heater Ducting

Construction: High strength sewn single-ply polyurethane coated polyester hose with a spring steel wire helix & heavy-duty PVC wearstrip.

Temperature Range (°F): -60°F to 400°F **Standard Color:** Black with Black Wearstrip

Size Range: 12" to 24" **Standard Length:** 25'

- Lock stitch construction creates better air flow & allows for better performance in lower & higher temperatures
- Light weight duct ideal for commercial & residential work area heating, cement drying & event tents
- Great compressibility & chemical, fuel & oil resistance
- Heavy-Duty wearstrip offers additional external abrasion & drag resistance (additional OEM colors available)
- Moisture resistant & UV stabilized to prevent mold & mildew
- Polyurethane coating increases puncture, abrasion & tear resistance
- Standard with wire ropes, belted cuffs & storage straps

FX-400

Bi-Directional Air Flow

Construction: High strength heat-welded single-ply polyurethane coated polyester hose with a spring steel wire helix & heavy-duty PVC wearstrip.

Temperature Range (°F): -60°F to 400°F **Standard Color:** Black with Black Wearstrip

Size Range: 12" to 24" **Standard Length:** 25'

- Bi-directional construction provides super air flow & excellent compressibility
- Light weight duct ideal for commercial & residential work area heating, cement drying & event tents
- Heavy-Duty wearstrip offers additional external abrasion & drag resistance (additional OEM colors available)
- Moisture resistant & UV stabilized to prevent mold & mildew
- Polyurethane coating increases puncture, abrasion & tear resistance
- Great chemical, fuel & oil resistance
- Standard with wire ropes, belted cuffs & storage straps

FX-400 SF

toll free: 800-343-0428

Email: sales@flexaust.com

www.flexaust.com



California Residents: **WARNING:** Cancer and Reproductive Harm-www.P65Warnings.ca.gov

Layflat A/C Ducting

Construction: High strength sewn single-ply PVC vinyl coated polyester hose.

Temperature Range (°F):
-20°F to 180°F

Standard Color: White

Additional Colors Available: ● ● ●

Size Range: 12" to 36"

Standard Length: 25', 50', 75', 100'

- Lock stitch construction creates better air flow & allows for better performance in lower & higher temperatures
- More economical choice than traditional wire-reinforced hose
- Light weight duct designed for dehumidification applications
- Great compressibility
- Moisture resistant & UV stabilized to prevent mold & mildew
- Dust resistant material creates an easy clean surface
- Flame retardant to UL 94V-0
- PVC coated polyester is superior to PVC laminated polyester products
- Standard with wire ropes, belted cuffs & tabs with grommets

FX-180 LF

Layflat Heater Ducting

Construction: High strength sewn single-ply polyurethane coated polyester hose.

Temperature Range (°F):
-60°F to 400°F

Standard Color: Black

Standard Length: 25', 50', 75', 100'

Size Range: 12" to 36"

- Lock stitch construction creates better air flow & allows for better performance in lower & higher temperatures
- More economical choice than traditional wire-reinforced hose
- Light weight duct ideal for commercial & residential work area heating, cement drying & event tents
- Great compressibility & chemical, fuel & oil resistance
- Moisture resistant & UV stabilized to prevent mold & mildew
- Polyurethane coating increases puncture, abrasion & tear resistance
- Standard with wire ropes, belted cuffs & tabs with grommets

FX-400 LF

Layflat Diffuser A/C Ducting

Construction: High strength sewn single-ply PVC vinyl coated polyester hose with 3" holes positioned upon request.

Temperature Range (°F):
-20°F to 180°F

Standard Color: White

Additional Colors Available: ● ● ●

Size Range: 12" to 36"

Standard Length: 25', 50', 75', 100'

- Lock stitch construction creates better air flow & allows for better performance in lower & higher temperatures
- More economical choice than traditional wire-reinforced hose
- Light weight duct designed for dehumidification applications
- Great compressibility
- Moisture resistant & UV stabilized to prevent mold & mildew
- Dust resistant material creates an easy clean surface
- Flame retardant to UL 94V-0
- PVC coated polyester is superior to PVC laminated polyester products
- Standard with wire ropes, belted cuffs & tabs with grommets

FX-180 DF

Layflat Diffuser Heater Ducting

Construction: High strength sewn single-ply polyurethane coated polyester hose with 3" holes positioned upon request.

Temperature Range (°F):
-60°F to 400°F

Standard Color: Black

Standard Length: 25', 50', 75', 100'

Size Range: 12" to 36"

- Lock stitch construction creates better air flow & allows for better performance in lower & higher temperatures
- More economical choice than traditional wire-reinforced hose
- Light weight duct ideal for commercial & residential work area heating, cement drying & event tents
- Great compressibility & chemical, fuel & oil resistance
- Moisture resistant & UV stabilized to prevent mold & mildew
- Polyurethane coating increases puncture, abrasion & tear resistance
- Standard with wire ropes, belted cuffs & tabs with grommets

FX-400 DF

toll free: 800-343-0428

Email: sales@flexaust.com

www.flexaust.com



California Residents: **WARNING:** Cancer and Reproductive Harm-www.P65Warnings.ca.gov

Dehumidification Ducting

Construction: High strength heat-welded single-ply PVC vinyl coated polyester hose with a spring steel wire helix & heavy-duty PVC wearstrip.

Temperature Range (°F):
-20°F to 180°F

Standard Color: Green with White Wearstrip

Standard Length: 25'

Size Range: 12" to 24"

- Bi-directional construction provides super air flow & good compressibility
- Light weight duct designed for water remediation & negative pressure applications
- Heavy-Duty wearstrip offers additional external abrasion & drag resistance
- Moisture resistant & UV stabilized to prevent mold & mildew
- Dust resistant material creates an easy clean surface
- Flame retardant to UL 94V-0
- PVC coated polyester is superior to PVC laminated polyester products
- Standard with wire ropes, belted cuffs & storage straps



FX-DU

Ceiling Tile Kit

Ideal for industrial portable air conditioning through a drop ceiling space. Provides excellent ventilation of exhaust & offers a great cooling source.

Kit Includes:

- White PVC vinyl coated polyester fabric hose, no wearstrip with enclosed belted cuff each end
- Hose available in ID sizes 12", 16" & 20"
- Hose available in 8' lengths
- Includes 2' square ceiling replacement tile
- 12 piece minimum required



END FINISHES & ACCESSORIES



Wire Rope/
Nylon Ring



Standard/Enclosed
Belted Cuff



Fabric Reducers/
Enlargers



Fabric 45° Connectors



Fabric 90° Connectors



Fabric Y's



Fabric T's



Fabric End Caps



Zipper Cuffs



J-Locks



Latch-Locks



Pin-Locks

toll free: 800-343-0428

Email: sales@flexaust.com

www.flexaust.com



California Residents: **WARNING:** Cancer and Reproductive Harm-www.P65Warnings.ca.gov